

Lilleshall Buildings, Gower Street Trading Estate, St. George's, TELFORD, Shropshire, TF2 9HW



Telephone: +44 (0)1952 620206 Facsimile: +44 (0)1952 620456

E-mail: sales@ic-international.com



Insulation Covers and Thermal Covers

Please contact us or Email us direct for a quote with your enquiry

BRIDELA™ **insulation covers and thermal insulation covers** are the leading brand of purpose designed reusable covers offering excellent insulation benefits for a wide variety of equipment including valves, flanges, calorifiers, strainers, separators, actuators, heat exchangers, elbow bends, etc.

These thermal insulation covers are a hugely popular and effective products and have been independently tested and certified to the stringent Class 'O' Building Regulation British Standard, conforming to BS 476 part 6 (fire propagation) and part 7 (Class 1 rating awarded for surface spread of flame).

Please click here to look at our product photographs to see the type of insulation/thermal covers we can manufacture.









Product Photographs

Why choose our Insulation Covers and Thermal Covers?

- Superb savings on energy bills
- Personnel protection from heat fatigue and possible skin burns
- Extremely easy fitting and quick removal for maintenance
- Covers are completely reusable
- Class 'O' certification
- Rapid pay-back/savings time
- Made from heat-resistant materials to withstand temperatures of up to 250°C/482°F (higher resistant covers available)
- Special covers available where acidic resistance required
- Safe to touch
- Drawstrings for effective end closure, where necessary
- Water repellent
- Protection against frost damage
- Competitively priced Please contact us for a quote
- Manufactured in the United Kingdom
- Offshore specification available

IC International is a United Kingdom manufacturing company who are certified (and independently audited) to the globally recognised international quality management standard ISO 9001

Special covers produced for individual applications

Fact

Uninsulated valves are liable to lose the heat equivalent of at least 1m/39" of the same bore size of uninsulated pipe

Source: Department of Environment Energy Efficiency Programme

Offshore specification available